

BARRAS NEUTRAS 600V

CONECTORES MECÁNICOS A TOPE

NEUTRAL BARS DUAL RATED

DUAL RATED



SPLICER/REDUCER

PARA CONDUCTORES DE “CU/AL”

Fabricadas con aleaciones de aluminio de alta conductividad y electroestañadas para proporcionar baja resistencia de contacto.

FOR USE WITH BOTH “AL/CU” CONDUCTORS

Are constructed from high conductivity auminum alloy and tin plated to provide low contact resistance.

No. Catálogo Catalog No.		Capacidad de conductor Wire Range	No. De Conex. No. of Circuit Taps	Altura Height	Longitud Length	Ancho Width
	CM 404	14-6 1.5-16 mm ²	4	0.500" 12.70 mm	1.566 " 39.77 mm	0.375 " 9.52 mm
	CM 406	14-6 1.5-16 mm ²	6	0.500 " 12.70 mm	2360 " 60 mm	0.375 " 9.52 mm
	CM 408	14-6 1.5-16 mm ²	8	0.500 " 12.70 mm	3.154 " 80.11 mm	0.375 " 9.52 mm
	CM 410	14-6 1.5-16 mm ²	10	0.500 " 12.70 mm	3.948 " 100.28 mm	0.375 " 9.52 mm
	CM 412	14-6 1.5-16 mm ²	12	0.500 " 12.70 mm	4.742 " 120.44 mm	0.375 " 9.52 mm
	CM 414	14-6 1.5-16 mm ²	14	0.500 " 12.70 mm	5.536 " 140.61 mm	0.375 " 9.52 mm
	CM 416	14-6 1.5-16 mm ²	16	0.500 " 12.70 mm	6.330 " 168.78 mm	0.375 " 9.52 mm
	CM 418	14-6 1.5-16 mm ²	18	0.500 " 12.70 mm	7.124 " 180.95 mm	0.375 " 9.52 mm
	CM 420	14-6 1.5-16 mm ²	20	0.500 " 12.70 mm	7.918 " 201.10 mm	0.375 " 9.52 mm
	CM 422	14-6 1.5-16 mm ²	22	0.500 " 12.70 mm	8.712 " 221.28 mm	0.375 " 9.52 mm
	CM 424	14-6 1.5-16 mm ²	24	0.500 " 12.70 mm	9.506 " 241.45 mm	0.375 " 9.52 mm
			No. Opresor No. Of Screws			
	CML 14-2	14-2 1.5-25 mm ²	2	0.550 " 13.97 mm	1.380 " 35.05 mm	0.535 " 13.59 mm
	CML 14-1/0	14-1/0 1.5-50 mm ²	2	0.790 " 20.06 mm	1.906 " 48.41 mm	0.600 " 15.24 mm
	CML 6-4/0	6-4/0 16-95 mm ²	2	1.000 " 25.40 mm	2.312 " 58.72 mm	1.000 " 25.40 mm
	CML 6-250	8-250 16-120 mm ²	4	1.000 " 25.40 mm	3.940 " 100 mm	1.000 " 25.40 mm
	CML 6-350	8-350 16-185 mm ²	4	1.125 " 28.57 mm	4.190 " 106.42 mm	1.000 " 25.40 mm
	CML 3/0-500	3/0-500 70-240 mm ²	4	1.562 " 39.67 mm	4.781 " 121.43 mm	1.375 " 34.92 mm
	CML 250-750	250-750 120-300 mm ²	4	1.562 " 39.67 mm	6.062 " 153.97 mm	1.375 " 34.92 mm