

REMATES CONFORMADOS PARA CABLE DE ACERO GALVANIZADO

DESCRIPCIÓN CORTA	CÓDIGO DE PARTE	DIÁMETRO DEL CABLE (mm)	LONGITUD L (mm)	RESISTENCIA (Kgs)	(d) DIÁMETRO DEL ALAMBRE EN PUL"	EMPAQUE JGOS / CAJAS	COLOR DE CÓDIGO
REMATE AG 3 (1/8)	AL-E-RAG-18	3.17	350	800	0.072	500	
REMATE AG 5 (3/16)	AL-E-RAG-316	4.76	558	1,650	0.086	200	
REMATE AG 6 (1/4)	AL-E-RAG-14	6.35	660	2,600	0.086	150	
REMATE AG 8 (5/16)	AL-E-RAG-516	7.94	780	3,900	0.105	100	
REMATE AG 9 (3/8)	AL-E-RAG-38	9.52	890	5,100	0.105	100	
REMATE AG 11 (7/16)	AL-E-RAG-716	11.11	955	7,800	0.105	60	
REMATE AG 12 (1/2)	AL-E-RAG-12	12.7	1010	9,000	0.165	50	

REMATES CONFORMADOS PARA CONDUCTORES AC

DESCRIPCIÓN CORTA	CÓDIGO DE PARTE	CONDUCTOR DESIGNACIÓN	DIAM.	RANGO DIAM. COND. MIN. MAX.	LONGITUD L (mm)	PESO / JUEGO APROX (Kg)	EMPAQUE JGOS / CAJAS	COLOR DE CÓDIGO
REMATE P ACSR 2	AL-E-R-02	SPARROW 6/1	8.01	7.37 8.25	609.6	0.149	150	
REMATE P ACSR 1/0	AL-E-R-10	RAVEN 6/1	10.11	9.27 10.39	660.4	0.280	100	
REMATE P ACSR 3/0	AL-E-R-30	PIGEON 6/1	12.75	11.71 13.11	812.8	0.390	50	
REMATE P ACSR 266	AL-E-R-266	PATRIDGE 26/7	16.28	15.77 17.37	1041.0	0.536	50	
REMATE P ACSR 336	AL-E-R-336	LINNET 26/7	18.29	16.61 18.77	990.0	0.678	30	
REMATE P ACSR 477	AL-E-R-477	HAWK 26/7	21.70	21.34 23.04	1397.0	0.858	20	