



CIRCUIT BREAKER T55 230/400V, 6KA,
1-POLE, C, 2A

General technical data:		
Current / with AC / Rated value	A	2
Tripping characteristic class		C
Type of voltage		AC/DC
Supply voltage		
• with AC / Rated value	V	400
• with single-phase operation / with AC / Rated value		
• with multi-phase operation / with AC / Rated value	V	400
Number of poles / Note		1P
Switching capacity current		
• acc. to IEC 60947-2 / Rated value	kA	10
• acc. to EN 60898 / Rated value	kA	6
Installation depth	mm	55
Number of width units		1
mounting position		any
Degree of pollution		3
Overvoltage category		3
• acc. to DIN EN 61346-2		
• acc. to DIN EN 81346-2		F

Certificates/approvals:

General Product Approval**Declaration of
Conformity**

CSA



GOST

[KTL](#)

UL



VDE



EG-Konf.

Test Certificates**other**[Special Test
Certificate](#)[Type Test
Certificates/Test
Report](#)[other](#)[Environmental
Confirmations](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.de/lowvoltage/mall>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WWW/view/en/5SX2102-7/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX2102-7**CAX-Online-Generator**<http://www.siemens.com/cax>

last change:

Oct 20, 2014