

Capacidad interruptiva

Tipo de interruptor	RMS Amperes Simétricos (KA)						IEC 947-2					
	UL 489 AIR (File E10848)						V AC (50/60 Hz)					
	V AC (50/60 Hz)			V DC			V AC (50/60 Hz)					
	240	480	600	250	500		220/240		380/415		500	
							Icu	Ics	Icu	Ics	Icu	Ics
FXD6	65	35	22	30 (2-P)	18 (3-P)		65	33	35	9	—	—
HFXD6	100	65	25	30 (2-P)	25 (3-P)		100	50	65	33	—	—

Ajuste de rango de disparo instantáneo

Amperaje del interruptor	Valores Nominales Instantáneos							
	±20% Baja Tol.	2	3	4	5	6	7	±20% Alta Tol.
125-150	800	900	1000	1100	1200	1300	1400	1500
175-200	900	1060	1210	1370	1520	1780	1930	2000
225-250	1100	1300	1500	1700	1900	2100	2300	2500

Zapatillas por 75 °C por Hilo

Material	Calibre de cable	Referencia	Número de catálogo
Al	(1) #6—350 kcmil Cu (1) #4—350 kcmil Al	TA1FD350A	A7B10000019949

Accesorios internos



Control de voltaje		Referencia	Número de catálogo
AC	DC		
Bobina de disparo			
120		S01FD60	A7B10000078762
Bobina de mínima tensión			
240		U03FD60	A7B10000078853
480		U06FD60	A7B10000078858
Contactos Auxiliares			
480		A01FD64	A7B10000078732