



Product designation

Product type designation

Number of poles

Operating voltage type

Enclosed switch
disconnecter
GAZ
Nr. 3
AC

Contact characteristics

IEC Conventional free air thermal current I _{th}	A	100
Rated insulation voltage U _i IEC/EN	V	1000
Rated impulse withstand voltage U _{imp}	kV	8

Operating current I_e

AC21A

400V	A	100
500V	A	100
690V	A	100

AC22A

400V	A	100
500V	A	100
690V	A	100

AC23A

400V	A	100
500V	A	80
690V	A	47

Power dissipation per pole max	W	4
--------------------------------	---	---

Rated operational power AC23A

400V	kW	55
690V	kW	45

Conditional short-circuit current (rms)	kA	50
---	----	----

Short-circuit protection with fuse	Class/A	gG100
------------------------------------	---------	-------

Making capacity AC23A 400V	A	1000
----------------------------	---	------

Breaking capacity AC23A 400V	A	800
------------------------------	---	-----

Mechanical life	cycles	30000
-----------------	--------	-------

Electrical life AC21A	cycles	30000
-----------------------	--------	-------

Mechanical features

Operating position

normal
allowable
Vertical plan
Any




Terminals

type		Pillar
width	mm	12.4
height	mm	10.4
screw		M8
tool		Metric Allen key 4


Tightening torque for terminals

min	Nm	5
max	Nm	6

	min	Ibin	45
	max	Ibin	54
Conductor section			
	IEC min	mm ²	4
	IEC max	mm ²	70
	AWG/kcmil min		12
	AWG/kcmil max		1
Ambient conditions			
Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-40
	max	°C	+70
Max altitude		m	3000
Resistance & Protection			
Frontal IP degree			IP65
IP degree of protection			IP65
Pollution degree			3
Dimensions			




Drilling for surface fixing



PG16 / M25
PG29 / M32
knockouts on top
and bottom

Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-3

Certifications

EAC

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnector