

VF-Ti/T Rod to C-Purlin Clip, Spring Steel, 3/8" Hole, Plain, 1/16"–1/4" Flange

CATALOG NUMBER

VF146T



CERTIFICATIONS




FEATURES

Hammer-on or install from the floor with the VAFT tool

Provides an attachment for nVent CADDY Speed Link assemblies, wire, S-hooks, or chain from purlin and bar joist

RODUCT ATTRIBUTES
Naterial: Spring Steel
inish: nVent CADDY Armour
lole Size (HS): 3/8"
lole Type: Plain
lange Thickness (FT): 0.0600" - 1/4"
leight (H): 5 3/16"
Static Load (F): 160lbf



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



This document is system-generated.

nVent.com/CADDY 2