




YC28C2, Copper C-Shape Connector

By Burndy
Catalog # YC28C2

CU Compression C Shape Compression Connector



Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Making Tap Or Parallel Copper Connections

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A;UL486B
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL 486A;UL486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Tap Range	6 Sol. - 2 Str
Conductor Type	Cu C Sol-Size

Dimensions

Dimension - L Length Overall mm	27 mm
Dimension - Height inch	1.65 in
Dimension - Height mm	0 mm
Dimension - Length Overall inch	1.07 in

General

Die Index	F or D3
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Plated	N
Type	YC-C Series
UPC 12 Digit	781810115756
UPC 14 Digit GTIN	00781810115756
Material	Copper
Plating Type	Unplated
UPC	781810115756

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	5800

Product Assets

[Catalog \[English\]](#)