



NUEVO MR16-LED/3W/30
MR16-LED/3W/65



MR16-SMDLED/3W/30
MR16-SMDLED/3W/65



MR16-COBLED/4W/30
MR16-COBLED/4W/65



MR16M-LED/4W/27
MR16M-LED/4W/65



NUEVO MR16-LED/5.5W/30
MR16-LED/5.5W/65

Producto	Potencia	Volts	Lúmenes	Temperatura de Color	IRC	Tiempo de Vida	Ángulo	Base	Dimensiones del Producto (BXA) +/-5 mm	Observaciones
MR16-LED/3W/30	3 W	100-240 V ~	250 lm	3000 K	80	15 000 h	36 °	GX5.3	50 mm x 45 mm	Ahorrador
MR16-LED/3W/65	3 W	100-240 V ~	250 lm	6500 K	80	15 000 h	36 °	GX5.3	50 mm x 45 mm	Ahorrador
MR16-SMDLED/3W/30	3 W	100-127 V ~	230 lm	3000 K	80	20 000 h	100 °	GX5.3	50 mm x 48 mm	Ahorrador
MR16-SMDLED/3W/65	3 W	100-127 V ~	230 lm	6500 K	80	20 000 h	100 °	GX5.3	50 mm x 48 mm	Ahorrador
MR16-COBLED/4W/30	4 W	100-240 V ~	200 lm	3000 K	80	25 000 h	38 °	GX5.3	50 mm x 50.3 mm	Ahorrador
MR16-COBLED/4W/65	4 W	100-240 V ~	200 lm	6500 K	80	25 000 h	38 °	GX5.3	50 mm x 50.3 mm	Ahorrador
MR16M-LED/4W/27	4 W	100-127 V ~	250 lm	2700 K	80	15 000 h	39 °	GX5.3	50 mm x 47 mm	Ahorrador
MR16M-LED/4W/65	4 W	100-127 V ~	250 lm	6500 K	80	15 000 h	39 °	GX5.3	50 mm x 47 mm	Ahorrador
MR16-LED/5.5W/30	5.5 W	100-240 V ~	350 lm	3000 K	80	15 000 h	36 °	GX5.3	50 mm x 45 mm	Ahorrador
MR16-LED/5.5W/65	5.5 W	100-240 V ~	350 lm	3000 K	80	15 000 h	36 °	GX5.3	50 mm x 45 mm	Ahorrador