


Hart lock industrial grade 30A locking devices

Product description

3-pole, 4-wire grounding
30A, 125/250V/AC
NEMA L14-30



AHL1430P



AHL1430C



AHL1430R

Industrial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	125/ 250	L14-30	Ultra grip straight body	0.38-1.16" (9.5-29.4mm)	BK & W	□ AHL1430P	□ AHL1430C	•	•

Industrial grade receptacles



Rating A	V/AC	NEMA	Description	Color	Single receptacle		
30	125/ 250	L14-30	Standard industrial	BK	□ AHL1430R	•	•
			Isolated ground	RN	□ IGL1430R*		•

*Not Fed Spec

Industrial grade flanged inlets & outlets



Rating A	V/AC	NEMA	Description	Color	Flanged inlet	Flanged outlet		
30	125/ 250	L14-30	Standard industrial	BK	□ AHL1430FI	—	•	•
			Standard industrial	BK & W	—	□ AHL1430FO**	•	•

**UL Listed only

Accessories for L14-30 locking devices

Description	Catalog no.		
Neoprene weather protective boot for 4-W & 5-W plugs	□ BL1	•	
Neoprene weather protective boot for 4-W & 5-W connectors	□ BL2	•	
Diecast aluminum single receptacle cover, vertical mount, for FS/FD boxes	□ 7420	•	•
Glass-filled nylon flanged inlet/outlet cover, vertical mount, for 30A devices	□ WP2	•	•



BL1



BL2



7420



WP2

Dimensional information:

C-76-C-78

Plug & connector specification information:

Ultra grip K14-30: C-84

Receptacle specification information:

K14-30: C-87

Isolated ground K14-30: C-87

Flanged inlet & flanged outlet specification information:

K14-30: C-78

Color information:

BK (Black), RN (Orange), W (White)

BK	RN	W
(Black)	(Orange)	(White)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-30

RoHS compliant - Page Q-30