

TUERCAS HEX grado 2

Galvanizadas



TH



CLAVE PEDIDO	TAMAÑO NOMINAL		PESO APROX x 100	EMPQ U / M	UNI
	mm	pulg			
TH 14	6.5 mm	1 / 4"	0.32 kg	500 / 4000	Cto
TH 56	8 mm	5 / 16"	0.45 kg	350 / 2800	Cto
TH 38	10 mm	3 / 8"	0.69 kg	250 / 2000	Cto
TH 12	13 mm	1 / 2"	1.64 kg	100 / 800	Cto
TH 58	16 mm	5 / 8"	3.21 kg	50 / 400	Cto
TH 34	19 mm	3 / 4"	5.32 kg	30 / 240	Cto

COPLES HEX

Galvanizados

CH



CLAVE PEDIDO	TAMAÑO NOMINAL		LARGO	EMPQ U / M	UNI
	mm	pulg			
CH 14 78	6.5 mm	1 / 4"	7 / 8"	200 / 1600	Pza
CH 56 100	8 mm	5 / 16"	1"	150 / 600	Pza
CH 38 118	10 mm	3 / 8"	1 1 / 8"	80 / 640	Pza
CH 12 114	13 mm	1 / 2"	1 1 / 4"	50 / 200	Pza

RONDANAS PLANAS COMERCIALES

Galvanizadas



RPL



CLAVE PEDIDO	TAMAÑO NOMINAL		EMPQ U / M	UNI
	mm	pulg		
RPL 36	5 mm	3 / 16"	2	Kilo
RPL 14	6.5 mm	1 / 4"	2	Kilo
RPL 56	8 mm	5 / 16"	2	Kilo
RPL 38	10 mm	3 / 8"	2	Kilo
RPL 12	13 mm	1 / 2"	2	Kilo
RPL 58	16 mm	5 / 8"	2	Kilo
RPL 34	19 mm	3 / 4"	2	Kilo

BARRAS ROSCADAS COMERCIALES

Acero 1008 galvanizado electrolíticamente



BR

CLAVE	CUERDA UNC		EMPQ	PESO APROX		UNI
PEDIDO	mm	pulg	U / M	x CTO		
Tramos de 1 metro						
BR 36 100	5 mm	3 / 16"	50	10.25 kg		Pza
BR 14 100	6.5 mm	1 / 4"	50	18.20 kg		Pza
BR 56 100	8 mm	5 / 16"	25	29.00 kg		Pza
BR 38 100	10 mm	3 / 8"	25	44.00 kg		Pza
BR 12 100	13 mm	1 / 2"	20	77.00 kg		Pza
BR 58 100	16 mm	5 / 8"	10			Pza
BR 34 100	19 mm	3 / 4"	10			Pza


Tramos de 3 metros

BR 14 300	6.5 mm	1 / 4"	50	54.00 kg	Pza
BR 56 300	8 mm	5 / 16"	25	90.00 kg	Pza
BR 38 300	10 mm	3 / 8"	25	130.00 kg	Pza
BR 12 300	13 mm	1 / 2"	15	239.00 kg	Pza
BR 58 300	16 mm	5 / 8"	5	473.00 kg	Pza
BR 34 300	19 mm	3 / 4"	5	682.00 kg	Pza

RONDANAS PLANAS INDUSTRIALES

Norma ANSI B.18.22.1-1995 (R2003)

Galvanizado electrolítico



RPI



CLAVE PEDIDO	TAMAÑO NOMINAL		DIMENSIONES mm			UNI
	mm	pulg	A	B	C	
RPI 14	6,5 mm	1 / 4"	1.5	7	19	Cto
RPI 38	10 mm	3 / 8"	1.9	10	25	Cto
RPI 12	13 mm	1 / 2"	2.7	13	32	Cto
RPI 58						Cto
RPI 34						Cto