

Product Selection

When Ordering Specify

- Catalog number

3

Type DB1 Flush Mount
Standard LeverType DB and DD
Surface Mounting
Standard LeverType DB1 Flush Mount
Knob OperatorType DB and DD
Surface Mounting
Knob Operator

Reversing Drum Type without Overload Relay

Maximum Horsepower

Three-Phase 200–230V		Single-Phase 115V 230V		DC 115V 230V		Size	Type of Operation	Lever Operator	Knob	Lever Operator	Knob
								Catalog Number		Catalog Number	
Three-Pole											
2	2	1-1/2	2	1	1	DB 1	Maintained ¹	9441H268	9441H269	9441H274	9441H275
							Maintained and Momentary ²	9441H271	9441H272	9441H276	—
3	5	1-1/2	2	1	1	DB 2	Maintained ¹	9441H353	9441H354	9441H347	—
							Maintained and Momentary ²	9441H356	9441H357	9441H349	9441H350
5	7-1/2	1-1/2	3	2	3	DD 1	Maintained ¹	9441H284	9441H285	9441H388	—
7-1/2	10	2	5	2	3	DD 2	Maintained ¹	9441H361	9441H363	9441H362	—

Notes

¹ These devices are field convertible from maintained both positions to momentary both positions.

² These devices are field convertible from maintained FORWARD and momentary REVERSE to momentary FORWARD and maintained REVERSE.