



Industrial grade 20A locking devices

Product description


2-pole, 3-wire grounding
20A, 480V/AC
NEMA L8-20




AHL820P



AHL820C



AHL820R



AHL820FI

Industrial grade plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	480	L8-20	Ultra grip straight body	0.38-1.00" (9.5-25.4mm)	BK & W	☐ AHL820P	☐ AHL820C		

Industrial grade receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle		
20	480	L8-20	Standard industrial	BK	☐ AHL820R ^a		
			Isolated ground	RN	☐ IGL820R*		

^aNot NOM cert, *Not Fed Spec

Industrial grade flanged inlets & outlets

Rating A	V/AC	NEMA	Description	Color	Flanged inlet	Flanged outlet	
20	480	L8-20	Standard industrial	BK	☐ AHL820FI	—	
			Standard industrial	BK & W	—	☐ AHL820FO ¹	

¹Only UL Listed & CSA certified

Accessories for NEMA L8-20 locking devices

Description	Catalog no.		
Neoprene weather protective boot for 20/30A, 3-W locking plug	☐ BM1		
Neoprene weather protective boot for 20/30A, 3-W locking connector	☐ BM2		
Diecast aluminum single receptacle cover, vertical mount, for FS/FD boxes	☐ 7420		



BM1

BM2

7420

Dimensional information: C-76-C-78

Plug & connector specification information:

L8-20: C-84

Receptacle specification information:

L8-20: C-87

Isolated ground L8-20: C-87

Flanged inlet & flanged outlet specification information:

L8-20: C-89

Color information:

BK (Black), RN (Orange), W (White)

(Black)	(Orange)	(White)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32