



Pan-Lug™ LCC6-14AW-L Comp. Lug, 6, Window, Tin Plt Cu, Strt, Two 1/4" Stud, PK50 LCC6-14AW-L

The LCC6-14AW-L Copper Compression Connector Lug, two-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The inspection window visually assures full conductor insertion. UL Listed and CSA Certified.

Specifications

Inside Diameter (In.)	0.22
Inside Diameter (mm)	5.58
Outer Diameter (In.)	0.31
Outer Diameter (mm)	7.87
Product Type	Copper Compression Connectors - Lugs
Lug Type	2 Stud Hole Lug
Base Material	Copper
Copper Code Conductor Size (AWG)	6
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	1/4
Stud Hole Size (mm)	6.4
Stud Hole Spacing (In.)	0.63
Stud Hole Spacing (mm)	16
Barrel Type	Long Barrel with Inspection Window
Barrel Length (In.)	1.07
Barrel Length (mm)	27.2
Tongue Type	Standard
Tongue Width (In.)	0.48
Tongue Width (mm)	12.2
Tongue Angle	Straight
Tongue Thickness (In.)	0.08
Tongue Thickness (mm)	2
Overall Length (In.)	2.49
Overall Length (mm)	63.2
Finish/Coating	Tin-Plated
Standards Met	C22.2 No. 65-13, 486A-486B File #E52164

Specifications (continued)

UL Temperature Rating (°C)	90
Maximum Voltage (kV)	35
Color Code	Blue
Panduit Die Index Number	P24
Burndy Die Index Number	7
T & B Die Index Number	7
Wire Strip Length (In.)	1-1/8
Wire Strip Length (mm)	28.6
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window, NEBS level 3.

Packaging Detail

UPC	07498379774
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0328
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000