



Pan-Lug™ LCC250-12-X Comp. Lug, 250, Tin Plt Copper, Strt, Two 1/2" Stud, PK10

LCC250-12-X

The LCC250-12-X Tin-Plated Copper Compression Lug Lug, two-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA Certified.

Specifications

Inside Diameter (In.)	0.63
Inside Diameter (mm)	16
Outer Diameter (In.)	0.77
Outer Diameter (mm)	19.55
Product Type	Copper Compression Connectors - Lugs
Lug Type	2 Stud Hole Lug
Base Material	Copper
Copper Code Conductor Size (kcmil)	250
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	1/2
Stud Hole Size (mm)	12.7
Stud Hole Spacing (In.)	1.75
Stud Hole Spacing (mm)	44.5
Barrel Type	Long Barrel without Inspection Window
Barrel Length (In.)	1.6
Barrel Length (mm)	40.6
Tongue Type	Standard
Tongue Width (In.)	1.17
Tongue Width (mm)	29.7
Tongue Angle	Straight
Tongue Thickness (In.)	0.14
Tongue Thickness (mm)	3.6
Overall Length (In.)	5.23
Overall Length (mm)	132.8
Finish/Coating	Tin-Plated
Standards Met	C22.2 No. 65-13, 486A-486B File #E52164

Specifications (continued)

UL Temperature Rating (°C)	90
Maximum Voltage (kV)	35
Color Code	Yellow
Panduit Die Index Number	P62
Burndy Die Index Number	16
T & B Die Index Number	16
Wire Strip Length (In.)	1-11/16
Wire Strip Length (mm)	42.9
Part Features	Tin plated to inhibit corrosion,color coded barrel, NEBS level 3.

Packaging Detail

UPC	07498390245
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0528
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000