



## Pan-Lug™ SCL6-L Comp. Splice, Long, Tin Plt Copper, PK50

### SCL6-L

The SCL6-L Copper Compression Lug Lug, standard barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. An inspection window aids to visually assure full conductor insertion, and the tin-plate material helps to inhibit corrosion. UL Listed and CSA Certified to 35 kV and temperature rated to 90°C.

### Specifications

Product Type	Compression Connectors - Splices
Sub Brand	Pan-Lug™
Copper Code Conductor Size (AWG)	6
Barrel Type	Standard
Maximum Voltage (kV)	35
Base Material	Copper
Standards Met	cULus Listed for Power and Grounding Applications; Meets UL467 Requirements for Grounding
Finish/Coating	Tin-Plated
Color Code	Blue
Burndy Die Index Number	7
Panduit Die Index Number	P24
Overall Length (In.)	2.38
Overall Length (mm)	60.45
Wire Strip Length (In.)	1-1/8
Wire Strip Length (mm)	28.6
UL Temperature Rating (°C)	90
Part Features	color coded barrel, internal wire stops, tin plated to inhibit corrosion, premium pull out strength, NEBS

### Packaging Detail

UPC	07498390431
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0328
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000