



Pan-Lug™ SCL3/0-X Comp. Splice, Long, 3/0, Tin-Plated Copper, PK10

SCL3/0-X

Copper butt splice, long barrel, 3/0 AWG wire.

Specifications

Product Type	Compression Connectors - Splices
Sub Brand	Pan-Lug™
Copper Code Conductor Size (AWG)	3/0
Barrel Type	Long
Maximum Voltage (kV)	35
Base Material	Copper
Standards Met	UL Listed for Power and Grounding Applications in the U.S. and Canada; Meets UL467 Requirements for Grounding
Finish/Coating	Tin-Plated
Color Code	Orange
Burndy Die Index Number	14
Panduit Die Index Number	P50
T & B Die Index Number	50
Overall Length (In.)	3.12
Overall Length (mm)	79.2
Wire Strip Length (In.)	1 1/2
Wire Strip Length (mm)	38.1
UL Temperature Rating (°C)	90
Part Features	color coded barrel, internal wire stops,tin plated to inhibit corrosion, premium pull out strength,NEBS

Packaging Detail

UPC	07498390435
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0328
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000