



Pan-Lug™ SCL4/0-X Comp. Splice, Long, 4/0, Tin-Plated Copper, PK10

SCL4/0-X

Copper butt splice, long barrel, 4/0 AWG wire.

Specifications

Product Type	Compression Connectors - Splices
Sub Brand	Pan-Lug™
Copper Code Conductor Size (AWG)	4/0
Barrel Type	Long
Maximum Voltage (kV)	35
Base Material	Copper
Standards Met	UL Listed for Power and Grounding Applications in the U.S. and Canada; Meets UL467 Requirements for Grounding
Finish/Coating	Tin-Plated
Color Code	Purple
Burndy Die Index Number	15
Panduit Die Index Number	P54
T & B Die Index Number	54
Overall Length (In.)	3.37
Overall Length (mm)	85.6
Wire Strip Length (In.)	1 5/8
Wire Strip Length (mm)	41.3
UL Temperature Rating (°C)	90
UL Temperature Rating (°F)	194
Part Features	color coded barrel, internal wire stops, tin plated to inhibit corrosion, premium pull out strength, NEBS

Packaging Detail

UPC	07498390440
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0328
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000