



Pan-Wrap™ SE50P-CR0 Braided Sleeving, Black, PET, 0.5" Nom Dia., 100', PK1

SE50P-CR0

The SE50P-CR0 Braided Sleeving provides continuous abrasion resistance for wires, cables, and tubing. The lightweight, durable protection is highly flexible, and the open weave will not trap heat or humidity. Complaint with U.S. and European passenger rail standards. Temperature range: -94°F – 257°F (-70°C – 125°C). Polyethylene Terephthalate. Nominal Diameter: 0.5" (12.7 mm), 100' (30.5 m) long. Color Black. 1 per package.

Specifications

Application	Provides Continuous Abrasion Protection for Wires, Cables, Hoses, and Tubing; Highly Flexible Open Weave will not Trap Heat or Humidity; Allows for Use with Irregular Shapes
Sub Brand	Pan-Wrap™
Material	Polyethylene Terephthalate (PET)
Flammability Rating	UL94V-0
Color	Black
Resistance Properties	Abrasion-Resistant
Standards Met	CSA Certified, Compliant with U.S. and European passenger rail standards EN-45545, UL Recognized E116868; RoHS Compliant
Maximum Diameter (In.)	0.75
Maximum Diameter (mm)	19.1
Maximum Operating Temperature (°C)	125
Minimum Operating Temperature (°C)	-70
Maximum Operating Temperature (°F)	257
Minimum Operating Temperature (°F)	-94
Nominal Diameter (In.)	0.5
Nominal Diameter (mm)	12.7
Overall Length (ft.)	100
Overall Length (m)	30.5
Product Type	Braided Expandable Sleeving
Maximum Bundle Diameter (In.)	0.75
Maximum Bundle Diameter (mm)	19.1
Minimum Bundle Diameter (In.)	0.25
Minimum Bundle Diameter (mm)	6.4

Specifications (continued)

Part Features	Provides continuous abrasion protection for wires, cables, hoses and tubing. Highly flexible open weave will not trap heat or humidity, allows for irregular shapes. Lightweight and durable protection. Complaint with U.S. and European passenger rail standards.
---------------	---

Packaging Detail

UPC	07498320238
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0955
Std. Ctn. Qty.	4
Std. Ctn. Volume (cf)	0.3821