



	MODELS 61®, 62®, 63®	WEATHERPROOF WIRE CONNECTORS		
FEATURES/BENEFITS:				
	<ul style="list-style-type: none">- EASY TO APPLY, PRE-FILLED TWIST-ON WIRE CONNECTORS- SILICONE-BASED SEALANT PROTECTS AGAINST MOISTURE AND CORROSION- UL LISTED TO 486G SEALED TWIST-ON WIRE CONNECTOR-FOR INTERIOR AND EXTERIOR DAMP/WET LOCATIONS- WIDE WIRE RANGE ENABLES USE ON VARIETY OF APPLICATIONS INCLUDING OUTDOOR POWER OUTLETS, OUTDOOR SIGNAGE, AND EXTERIOR AREA LIGHTING			
ELECTRICAL:		APPLICATION TOOLING:		
VOLTAGE: GENERAL: 600 V MAX SIGNS/LUMINAIRES: 1000 V MAX		<ul style="list-style-type: none">- Spin-Twist® Wire Connector Socket		
PHYSICAL:		STANDARDS & SPECIFICATIONS:		
HOUSING: THERMOPLASTIC POLYESTER INSERT: STEEL PLATING: ZINC TEMPERATURE: 105 C (221 F) SEALANT 100% SILICONE		UL 486C UL 486G SEALED TWIST-ON WIRE CONNECTOR UL 94V-2 FLAME RATING CSA- C22.2 NO. 188 CSA- C22.2 NO. 198.2 DAMP & WET LOCATIONS RoHS COMPLIANT IEC 998-2-4 IP 68 TESTED		
WIRE RANGE: <ul style="list-style-type: none">- Solid and/or stranded wire combinations unless stated otherwise- Consult factory for other combinations not listed				
MODEL 61® (GRAY/ORANGE)	MODEL 62® (GRAY/RED)	MODEL 63® (GRAY/DARK BLUE)		
STRIP LENGTH: 3/8" (9,5mm)	STRIP LENGTH: 5/8" (15,9mm)	STRIP LENGTH: 5/8" (15,9mm)		
1 or 2 #14 2 #16 1 to 4 # 18 Str. 2 to 4 #18 Sol. 2 to 4 #20	1 to 3#10 1 to 4 #12 Sol. 1 to 3 #12 1 to 5 #14 1 to 6 #16 2 to 6 #18	1 or 2 #8 2 to 5 #10 2 to 6 #12 1 to 3 #14		
DIMENSIONS:				
				
ORDERING INFO:				
CATALOG # 30-1361 30-1362 30-1363	MODEL 61® 62® 63®	COLOR: Gray/Orange Gray/Red Gray/Dark Blue	PACKAGE TYPE: Box of 1,000 Box of 1,000 Box of 1,000	WEIGHT LBS (KG): 5.3 (2.4) 12.3 (5.6) 17.9 (8.1)
FACTORY CONTACT:			SALES CONTACT:	
IDEAL INDUSTRIES, INC. BECKER PLACE SYCAMORE IL USA 60178 P: 1-800-435-0705 F: 1-888-222-6140 E: contactus@idealindustries.com				